

FIRE STOPPING

BY NORSEAL

PIPE COLLAR

PYROPLEX



Application

Around plastic pipes that penetrate concrete and masonry walls and floors

Soil, waste and drainage 'above ground'

Plasterboard partition PPC25 - PPC160 only (400 series only)

Fixing

M8 x 65mm Sleeve anchors or 50mm (minimum) expanding bolts

Performance

Fire tested to BS 476-20 and BS EN 1366-3

CE Marked (1121-CPR-JA5002)

Certifire CF635

Classified to BS EN 13501-2

ETA - 15/0136

Colour

Silver grey

200 SERIES PIPE COLLAR (2 HOUR)

Material

200 series- Galvanised steel outer casing, Pyroplex graphite

Sizes (mm) - external pipe diameter

55, 75, 82, 110, 160

Order code

COL + Size + -2H

eg. COL55-2H (55mm, 2 hours)

400 SERIES PIPE COLLAR (4 HOUR)

Material

400 series- Stainless steel outer casing, Pyroplex graphite


Sizes (mm) - external pipe diameter

25, 32, 40, 48, 55, 68, 82, 90, 110, 125, 135, 160, 200, 225, 250, 315, 350, 400

Order code

COL + Size + -4H

eg. COL55-4H (55mm, 4 hours)

 5 Regents Drive
Prudhoe
Northumberland
NE42 6PX



norseal.co.uk



firestopping@norseal.co.uk



01661 520 930

Registered at Companies House Cardiff No. 04317595 VAT Reg. No. 733 9466 08